

PRODUCT DESCRIPTION :

A oil modified polyurethane mixed for use wood grain filler which is friendly worked and has excellent filling and " HOLD-OUT " characteristics. A high viscosity product and high solid content product.

RECOMMENDED USE :

Wood stain 200 is designed for use with poen-grained timber on furniture, panelling and joinery to produce a uniformly smoot and tough finish once sealed and topcoated with lacquer, acid curing, polyurethane, ect.

PHYSICAL DATA :

Finish	Flat
Vehicle type	Oil modified polyuethane resin
No. of component	1
Colour	NEUTRAL , ALL COLOUR
Surface	Wood
Solid content (%)	80%
Specific gravity (25 °C)	1.7-1.8
Flash point	75 + 2 °C

APPLICATION DATA :

APPLICATION	Stir thoroughly and then apply liberally with a clean cloth pad, rubbing well into the grain and leaving an excess on the surface. Allow to stand 3-5 minutes, until wet sheen begins to dull. Remove the excess filler with clean cloth, rubbing across the grain, after that, rub lightly along the grain to eliminate cross streaks.
SURFACE PREPARATION	Surface to be painted must be thoroughly cleaned and free from and traces of oil & grease loose wood grain.
APPROXIMATED COVERAGE AREA	9 - 11 Sq.M / KG.
THINNER	THINNER 4K NO. 2001
CLEANER	THINNER 4K NO. 17
DRYING TIME (30 °C)	To touch 5 - 10 minutes To recoat 120 - 180 minutes
Drying time are dependent on thickness apply, temperature and humidity.	

STORAGE AND HANDLING :

STORAGE	The product must be store in well ventilated place protected from high temperature. Container must be kept tightly closed .
HANDIND	Handle with care. Stir well be for use.
PACKING	25 kgs

HEALTH AND SAFETY :

Avoid contact with skin and eyes wear. Wear suitable protective clothing such as overalls during painting.
Avoid skin contact. Spillage on skin should immediately be remove with soap and water. Eyes should be flushed flushed with water and medical attention sought immediately.