

PRODUCT DESCRIPTION :

Superflor HS Clear is a solvent free , two -component epoxy hardening compound which has durable abrasion and heat resistant finish .

RECOMMENDED USE :

Use to repair damaged concrete construction , suited for seal and joining of concrete or woodwork.

PHYSICAL DATA :

Colour	Clear		
Volume Solid (%)	100	Drying time @ 25 deg C	
Specific gravity	1.15-1.7	Dry to touch	4-5 hours
Surface	Concrete , wood	Dry to hard	10-12 hours
Flash point	115 + 2 deg C	Cured to hard	2-7 days
Film thickness recommended		-Recommended film thickness	
Theoretical coverage cal.		-Good ventilation	
		- Dependent on temperature and humidity	

APPLICATION DATA :

Application method	Trowel
Mixi (by weight)	A : B ; 3 : 2 by weight
Potlife	30 minutes @ 25 deg C
Cleaner	Thinner 4K No. 65

SURFACE PREPARATION :

Surface must be clean , Remove all dirt , grease and other foreign matter by cleaner and sandblasting , or mechanical abrasion . Remove water and dust from the surfaces.

STORAGE AND HANDLING :

Storage	The product must be store in well ventilated place protected from high temperature. Container must be kept tightly closed .
Handling	Handle with care . Stir well be for use .
Packing	part A = 2.1 kg , part B = 2x 0.7 kg

HEALTH AND SAFETY :

Avoid contact with skin and eyes wear . Wear suitable protective clothing such as overalls during painting.
 Avoid skin contact . Spillage on skin should immediately be remove with soap and water.
 Eyes should be flushed with water and medical attention sought immediately.