

PRODUCT DESCRIPTION :

Unique Roof Protection is a acrylic water base single pack with highly efficient saving elastomeric coating designed to both insulating and water proofing. It is base on elastomeric polymer blended white special ceramic micro spheres that acts as a thermally efficient blanket. Non toxic and environmental friendly.

RECOMMENDED USE

For use rendered cement, fiber board, concrete and masonry surfaces suitable for most exterior building surfaces.

PHYSICAL DATA

| | |
|----------------------------|----------------------|
| Colour | White |
| Solid content (%) | 62 ± 2 |
| Specific gravity | 0.90-0.92 |
| Gloss | Low sheen |
| Surface | Concrete |
| Film thickness recommended | 200 microns dry film |
| Theoretical coverage | 50 sq. m / 5 us.gl |

SYSTEM RECOMMENED

- Superflor BH Clear
- Unique Roof Protection
- Unique Flex Protection

APPLICATION DATA

| | |
|--------------------|----------------------------------|
| Application method | Brush , Roller and Airless spray |
| Cleaner/Thinner | Water |

SURFACE PREPARATION

Surface is clean and dry. All loose, and flaking paint must be removed.

STORAGE AND HANDLING

| | |
|---------|---|
| Storage | The product must be store in well ventilated place protected from high temperature. Container must be kept tightly closed . |
| Handing | Handle with care. Stir well be for use. |
| Packing | 5 US gal. |

HEALTH AND SAFETY

Avoid contact with skin and eyes wear. Wear suitable protective clothing such as overalls during painting.
 Avoid skin contact. Spillage on skin should immediately be remove with soap and water. Eyes should be flushed flushed with water and medical attention sought immediately.